EcoMo Auto Operation High Speed Hand Dryer

High Speed Hand Dryer Solutions



SPECIFICATIONS

SPECIFICA					
Cover/Specify	3.0mm thick molded Antibacterial ABS Plastic Silver: ML_ECOMOROUND_SIL Black: ML_ECOMOROUND_BLK	Ť			\square
Motor	350-700W, 12,000 - 18,000 R.P.M, Adjustable Brush Motor		por		
Motor Thermal Protection	Auto resetting thermostat turns unit off, 240V/277V at 95°C	14	(()))H	
Power Use	220-240 Vac, 50/60 Hz, 6.1-6.7A, 1.34 -1.6Kw		11		
Standby Power	0.3 - 0.4W		11		
LED Colour	Standby: Red, Active: Blue	624.5	9		
Sound Level	Min. 72.2dB to 75.4dB Max. at 1m				
Drying Time	10-15 seconds	(24.59)			
Drip Proof	IP21 or IP24 (optional)				
Heater Element	ON/OFF switch available, Power 450-900W depending on air speed				
Heater Thermal Protection	Auto resetting thermostat turns off unit at 85°C, Thermal cut-off at 142°C				
Warm Air Speed	75-90m/s (adjustable)				
Air Output	55°C – Ambient Temp. 25°C		-		
Timer Protection	60 seconds auto shut off	¥			
Circuit/ Sensor Range	Circuit Operation – Infrared Automatic, Self-Adjusting Sensor Range Standard 170mm ± 20mm adjustable	H-	- 322	—₩	⊮ 185 →
Case Security	SS theft resistant hex drive screws (hex key supplied)		(12.68)		(7.28)
Net Weight & Dimensions	9.4kg 322mm W x 624.5mm H x 185mm D				
Filter	Super filter assembly consisting of Antibacterial Filter • Carbon Filter • HEPA Filter				
Warranty	5 Year Warranty (3 Years Parts & Labour +2 Years Parts Only)	Safety Approvo	ds CB C	E 🚇 🗟	EMC LVD
Notes	* Unit can be hard wired by electrician or used with a cord and plug provided * This unit is deemed disabled complaint when installed with AS1428.1 Guidelines.	Green Certificat		GreenSpec W	EEE RoHS

