

ML771-Series Framed Mirror

Note

This product is to be installed by suitably qualified persons, in a fit-for-purpose application, to suitable materials, using suitable fixings, and complying with any relevant codes.

Dimensions

- **ML771:** 460mmW x 610mmH
- **ML771_1:** 460mmW x 760mmH
- **ML771_2:** 460mmW x 910mmH
- **ML771_3:** 610mmW x 760mmH
- **ML771_4:** 610mmW x 910mmH
- **ML771_5:** 450mmW x 1000mmH
- **ML771_6:** 600mmW x 1000mmH

Hardware Provided

- 2x French cleat hangers (Z-bars)
- 2x Wall Brackets
- 4x Screws
- 4x Wall Plugs

Before Installation

- Inspect the product. If there is any damage or missing parts, do not install the product and contact your place of purchase.
- Ensure the surface you wish to mount the mirror to is flat.
- Ensure the surface you wish to mount the mirror to is either solid or has adequate in-wall support.
- Check that there will be adequate clearance (approximately 25mm) above the mirror for it to be lifted on and off the wall brackets.



ML771_5 and ML771_6 are accessible compliant when installed in accordance with AS 1428.1 guidelines.

Installation Instructions

Placement may be subject to regulations/codes and architectural drawings. Correct positioning is the responsibility of the installer.

- Remove the two French cleat hangers from the rear of the mirror.
- Place the mirror against the wall to determine the desired height and use the hangers to mark the locations of the mounting holes, checking that they are level.
- Install suitable fasteners into the wall at the marked locations and attach the hangers. Re-check the level before tightening the fasteners.
- Place the mirror onto the hangers by centring it horizontally with the hangers and lowering it down against the wall to firmly secure both the hangers on the wall and the corresponding hangers on the mirror together.
To deter vandals, run a bead of silicone across both sets of hangers prior to placing the mirror on the hangers.
- If the mirror isn't perfectly centred, you can slide it left or right along the hanger a little.

Note Regarding Accessible Compliance:

"In all sanitary facilities, the mirror shall be provided and located either above or adjacent to the washbasin. Where located above the washbasin, the mirror shall extend from a height of not more than 900 mm to a height of not less than 1 850 mm above the plane of the finished floor. Where located adjacent to a washbasin, the mirror, shall extend from a height of not more than 780 mm to a height of not less than 1 850 mm above the plane of the finished floor. No mirror shall be less than 350 mm wide. All dimensions apply to the reflective surface of the mirror. The reflective surface shall be vertical. In an accessible sole occupancy unit, a mirror shall be centred over the washbasin."

- AS 1428.1:2021 clause 12.4.1

Technical recommendations and installation advice from Metlam Australia Pty Ltd are general in nature and provided in good faith without warranty. Metlam disclaims all liability for errors, omissions, or damage resulting from improper installation or maintenance. All products must be installed by qualified tradespeople and maintained by competent personnel. It is the installer's responsibility to conduct thorough pre-installation assessments; Metlam Australia will not enter into post-installation disputes regarding positioning, functionality, or external factors affecting performance.