

MLS Sign

Note

This product is to be installed by suitably qualified persons, in a fit-for-purpose application, to suitable materials, using suitable fixings, and complying with any relevant codes.

Hardware Provided

Please be aware that adhesives are not included.

Before Installation

- Inspect the product. If there is any damage or missing parts, do not install the product and contact your place of purchase.
- Ensure the surface you wish to mount the sign to is flat.
- Thoroughly clean and dry the surface you wish to mount the sign to.



This product is accessible compliant when installed in accordance with AS 1428.1 guidelines.

The photographs and line drawings of the products presented above are representational only.
Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.

Installation Instructions

Placement may be subject to regulations/codes and architectural drawings. Correct positioning is the responsibility of the installer.

1. Place the sign at the desired height, and checking that it is level, mark the location.
2. Apply an appropriate double-sided tape and/or neutral cure silicone to the rear of the sign and mount it to the marked location.
Do not screw the sign to the surface.

Note Regarding Compliance:

"Signs including symbols, numbering and lettering must be designed and installed as follows:

- a. *Braille and tactile components of a sign must be located not less than 1200 mm and not higher than 1600 mm above the floor or ground surface.*
- b. *Signs with single lines of characters must have the line of tactile characters not less than 1250 mm and not higher than 1350 mm above the floor or ground surface.*
- c. *Signs identifying rooms containing features or facilities listed in D4D7 must be located—*
 - i. *on the wall on the latch side of the door with the leading edge of the sign located between 50 mm and 300 mm from the architrave; and*
 - ii. *where (i) is not possible, the sign may be placed on the door itself.*
- d. *Signs identifying a door required by E4D5 to be provided with an exit sign must be located—*
 - i. *on the side that faces a person seeking egress; and*
 - ii. *on the wall on the latch side of the door with the leading edge of the sign located between 50 mm and 300 mm from the architrave; and*
 - iii. *where (ii) is not possible, the sign may be placed on the door itself."*

- BCA/NCC 2022 specification D3.6: 2 clause S15C2

"The following applies to luminance contrast:

1. *The background, negative space, fill of a sign or border with a minimum width of 5 mm must have a luminance contrast with the surface on which it is mounted of not less than 30%.*
2. *Tactile characters, icons and symbols must have a minimum luminance contrast of 30% to the surface on which the characters are mounted.*
3. *Luminance contrasts must be met under the lighting conditions in which the sign is to be located."*

- BCA/NCC 2022 specification D3.6: 4 clause S15C4

Technical recommendations and installation advice from Metlam Australia Pty Ltd are general in nature and provided in good faith without warranty. Metlam disclaims all liability for errors, omissions, or damage resulting from improper installation or maintenance. All products must be installed by qualified tradespeople and maintained by competent personnel. It is the installer's responsibility to conduct thorough pre-installation assessments; Metlam Australia will not enter into post-installation disputes regarding positioning, functionality, or external factors affecting performance.

The photographs and line drawings of the products presented above are representational only.

Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.